

**GIFFORD, KRASS, SPRINKLE,
ANDERSON & CITKOWSKI, P.C.
2701 Troy Center Drive, Suite 330
Post Office Box 7021
Troy, Michigan 48007-7021**

**(248) 647-6000
FACSIMILE (248) 647-5210
info@patlaw.com**

FACSIMILE TRANSMISSION

Sender's Initials EN

TO: Examiner Gami

FACSIMILE NO.: 571-270-2035

FROM: Douglas W. Sprinkle

PAGES TRANSMITTED (INCLUDING COVER SHEET): 3

ORIGINAL DOCUMENTS WILL ☐ WILL NOT ☒ FOLLOW BY MAIL

RE: Serial No. 10/575,544

MESSAGE: Please see the attached proposed amendment.

Information contained in this facsimile may be PRIVILEGED and CONFIDENTIAL. It is intended only for the use of the person or entity named above. If you are not the intended recipient, you are hereby notified that any dissemination, distribution, or copying of this communication is neither intended nor permissible. If this facsimile has been received in error, please notify us immediately (call collect) and return the facsimile to us.

Docket No.: MFA-20202/04
(PATENT)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of:
Reinhard Keller

Application No.: 10/575,544

Confirmation No.: 5662

Filed: May 18, 2006

Art Unit: 2121

For: CONTROL FOR A MACHINE FOR THE
MANUFACTURE OF PAPER PADDING

Examiner: Tejal Gami

CLAIMS FOR DISCUSSION PURPOSES ONLY

1. (Currently amended) A control (10, 40) for a machine for the manufacture of paper padding, wherein the machine comprises a drive motor having a cutting device and a shaping device to form a piece of padding from a paper web and to cut it off in a desired length, comprising

an input means (18) to input a desired length of padding;

a control unit (10, 40) having a memory to control the drive motor in response to the input means (18),

wherein an activation of the input means (18) starts the drive motor and a deactivation of the input means triggers a cutting procedure and stops the drive motor so that the time period of the activation of the input means corresponds to the length of padding produced, and

wherein the control unit (10, 40) automatically stores said length of padding produced in the memory on deactivation of the input means (18) and makes it available for a further call up upon momentary activation of said input means such that the length of padding just produced can is automatically ~~be~~ reproduced on request.

14. (Currently amended) A machine for the manufacture of paper padding, comprising:

a drive motor having a cutting device and a shaping device to shape a piece of padding from a paper web and to cut it off in a desired length; and

a control comprising:

an input means (18) to input a desired length of padding;

a control unit (10, 40) having a memory to control the drive motor in response to the input means (18),

wherein an activation of the input means (18) starts the drive motor and a deactivation of the input means triggers a cutting procedure and stops the drive motor so that the time period of the activation of the input means corresponds to the length of padding produced, and

wherein the control unit (10, 40) automatically stores the length of padding produced in the memory on deactivation of the input means (18) and makes it available for a further call up upon momentary activation of said input means such that the length of padding just produced is automatically reproduced upon request.